

Chemical Use Requirements for Pools without Electronic Monitoring Devices

Pool Type	Minimum Chlorine	Combined Chlorine	Minimum Bromine	рН	Alkalinity
Whirlpool Exercise Pool Therapy Pool	3 PPM 6 PPM with stabilizer	Less than 0.8 PPM	4 PPM	7.4-7.6	60-180 PPM
All other types of pools	1 PPM 2 PPM with stabilizer	Less than 0.6 PPM	3 PPM	7.4-7.6	60-180 PPM
Wading Pool	2 PPM 4 PPM with stabilizer	Less than 0.6 PPM	4 PPM	7.4-7.6	60-180 PPM
Interactive Play Attractions, Plunge & Wave Pools, Waterslides	2 PPM 4 PPM with Stabilizer	Less than 0.6 PPM	3 PPM	7.4-7.6	60-180 PPM

- Cyanuric acid use in outdoor pools may not exceed 30 PPM
- Whirlpool temperature may not exceed 104°F
- Outdoor swimming pool temperature may not fall below 65°F

*Adjust temperature, alkalinity, and hardness to maintain a saturation index between -.3 and .3





List of Required Documents to be Maintained Onsite

These files to be maintained onsite permanently

- Pool Architectural Plans (if built after 7/1/2023)
- Copy of ATCP 76
- Pump manufacturer's pump performance curve
- Drain covers' spec sheets
- VGBA drain cover replacement log (provided by department)
- Instruction manual for pool's filter and other necessary equipment
- CDC's fecal incident response guidelines
- Death-injury-illness report (7 years after incident)
- Fecal-vomit-blood incident response report (2 years after incident)
- Daily chemical testing logs (provided by department kept for 2 years)
- Anti-entrapment device or system testing (2 years when applicable)
- Any lab bacteriological reports (2 years)

